

MADE IN KOREA

Thermal Ink Jet Printer

300dpi Text, Image and Barcode marking hp Technology solvent / water based cartridge Simple and Lightweight Design 7" Touch Panel Display

Product Info

Introducing the new Inter Mac own RED TIJ (Thermal Ink Jet) marking system. RED TIJ printer uses hp Technology solvent based ink cartridge to print on non-porous surface (PP, PE, Vinyl, Steel, Glass and etc.) and water based ink cartridge to print on porous surface (carton box, paper and etc.). There are many kinds of TIJ systems, but RED TIJ is more functional, cost-effective, and even fashionable. Simple, handy and lightweight design allows easy-installation anywhere. In addition, it can be an important factor which can lower the manufacturing and maintenance cost.

RED TIJ system provides a Window based graphic user interface to help users operate the system without trouble. Software menu is available in a variety of languages with 7" touch panel display.









Size and Weight

Printhead Size 129X107X30mm

Printhead Weight 386g, 482g(including a cartridge)

Controller Size 203X113X42mm

Controller Weight 924g Display Size 7inches

Print Spec

Printhead Capability TIJ.1 (1 head), TIJ.2 (2 heads)

Resolution 300DPI, 600DPI

Print Speed Max. 60m/min (300DPI)

Print Height 1-12.7mm

Storage Capacity 1,000 messages

Message Text, Barcode, Image, Auto Date/Time, Counter, Shift Code

Barcode QR Code, DataMatrix, CODE128, CODE39, CODE93, CODE20F5, EAN13, UPCA, UPCE **Language** English, Chinese, Korean, Japanese, Vietnamese, Italian, Turkish, Spanish, Arabic, Persian,

Portuguese, Lithuanian, German, French, Russian, Dutch, Indonesian, Hindi, Malaysia, Bangla, Thai, Rumanian

Font Type Gulim, Arial / Importing an external font Date Type Production Date, Expiration Date, Julian Date

Ink Spec

Manufacturer HP original Cartridge(hp TIJ 2.5) Ink Type Solvent, Aqueous, Pigment, UV Ink Color Black, Red, Blue, Green, White, Yellow Marking Surface All material is available

Product Spec

Power AC90V-240V / 50-60Hz(Dedicated AC)
Interface 7" (800X480mm) Color LCD Touch Screen
Connection Port Photo Sensor, Warning Light, BCD,
RS232, Encoder, USB

Backup/Recovery USB


Ink management Auto Configuration of Ink residual and Ink Type


Operating Temperature −10−45°C Operating Humidity 10-85%RH

Certificate CE, FCC


Dimension


RED TIJ CONTROLLER





RED TIJ PRINTHEAD





Application





